

LIST OF FIGURES – VOL. III

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.5.1-1	This block diagram illustrates how the Prometheus ELMO pulses are beam-divided, amplified, accumulated, pulse-compressed, and focused onto the DT target.....	6.5.1-2
6.5.1-2	The 1 J output pulse from the ELMO is divided into 1020 beamlines, amplified by ELPs, ELDs, and ELPAs. The Stokes seeds are generated and injected into the Raman accumulators along with the main output beams.	6.5.1-3
6.5.1-3	Following the conversion of the excimer pump beams in the Raman accumulators, the long 250-ns (for EDELs) or 500-ns (for EBELs) pulses are injected into the SBS pulse compressor cells where ~65% of the energy is converted into a 6-ns pulse using a ramped Stokes SBS seed.....	6.5.1-4
6.5.1-4	The output pulse of Prometheus laser driver is initiated at the ELMO, amplified by the EDELs, Raman converted in 60 Accumulator Cells, Pulse Compressed in 60 SBS Cells, and Focused onto the Direct-Drive Target with the Final Focus Mirror and the Grazing Incidence Mirror.....	6.5.1-6
6.5.1-5	The electric discharge excimer laser (EDEL) excitation geometry provides for direct excitation of the KrF excimer via electric discharges between electrodes immersed in preionized volumes.	6.5.1-9
6.5.1-6	The electron-beam excited excimer laser (EBEL) excitation geometry permits larger volumetric excitation of the KrF excimer via direct e-beam excitation transmitted through a Hibachi and foil vacuum barrier.	6.5.1-11
6.5.1-7	Pulsed power configuration for the EDEL version of the ELPA.....	6.5.1-16
6.5.1-8	Each Raman accumulator subsystem consists of a local Raman oscillator (LRO), a Raman preamplifier, and a recollimation telescope generating 120x120 cm Raman Stokes seed beam of 30 J to drive the Raman accumulator cells.	6.5.1-17
6.5.1-9	Injection of the Stokes seed into the Raman accumulator cell permits the efficient extraction of the excimer pump beams into a 100 kJ beam having an aperture of 1.2x1.2 m.....	6.5.1-20
6.5.1-10	The RAC conversion efficiency is dependent upon the CRAM angle, hydrogen gas density, and distance along the accumulator axis assuming a 5 GHz bandwidth, 250 nm pump beam, 100 kJ energy in 250 ns pulse duration.....	6.5.1-21
6.5.1-11	The complex temporal shape of the direct-drive laser driver pulse consists of a ramped, 80 ns precursor pulse followed by a short, 6 ns main pulse.....	6.5.1-24
6.5.1-12	By frequency-"chirping" the leading edge of the SBS pumping pulse and reflecting it back upon the incoming pulse within an SF cell, it is possible to compress the RAC output pulse from 250 ns (or 500 ns) down to short pulse durations.....	6.5.1-26
6.5.1-13	Pulse compression in the SBS pulse compressor.....	6.5.1-27
6.5.1-14	By use of a large aperture Pockels cell and a delay line, the short main pulse and long precursor pulses are temporally inverted	6.5.1-28
6.5.1-15	With fast Pockels cells and additional delay lines, additional temporal tailoring of the pulse shape is possible.	6.5.1-29
6.5.1-16	A variety of compressed pulse shapes could be achieved using a 600 ns Raman pump beam, 100 kJ energy, 1 amagat SF ₆ density, and the indicated Stokes seed ramp ratios.....	6.5.1-30
6.5.1-17	Further compressed pulse shapes can be generated using a 250 ns Raman pump beam at 250 nm, 120 kJ of energy, 2 amagat SF ₆ density, 1x1 meter aperture and the indicated Stokes seed ramp ratios	6.5.1-30
6.5.1-18	The SBS pulse compressor efficiency for 5 GHz 250 ns 120 kJ Raman pulses at 250 nm decreases as the Stokes seed ramp ratio increases	6.5.1-31
6.5.1-19	Temporal developments of depleted pump pulses emerging from SBS pulse compressor for 5 GHz, 100 kJ, 500 ns RAC pulses in 1 amagat of SF ₆ , 1x1 m apertures	6.5.1-32
6.5.1-20	Temporal developments of depleted pump pulses from SBS pulse compressor for 5 GHz, 120 kJ, 250 nm pump, 250 ns pulse duration RAC pulses in 2 amagat of SF ₆	6.5.1-32

LIST OF FIGURES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.5.1-21	By utilizing a figured meniscus dichroic focusing mirror, it is possible to image the shine shield onto a highly magnified CCD array	6.5.1-35
6.5.1-22	The incident beam from the E/O Switchyard is focused through and shielding by the collimating mirror, refocused by the focusing mirror, and beam directed onto the target by the grazing incidence mirror	6.5.1-36
6.5.1-23	The single beam Prometheus laser intensity as a function of distance from a 6 mm diameter direct drive target with the beam diameter = target diameter at the target for a 100 kJ beam in a 6 ns pulse	6.5.1-39
6.5.1-24	Schematic of Prompt Radiation for D/T Target Ablating Plasma from Reactor Chamber First Wall	6.5.1-42
6.5.1-25	Schematic of Placement of Final Focusing Optics, Magnetic Deflector, Rotating Mechanical Shutter, and Input Laser Pulse Relative to Target Chamber	6.5.1-43
6.5.1-26	Target Debris Velocity Spectra for Bare D/T Target	6.5.1-45
6.5.1-27	Reflectivities at Normal Incidence	6.5.1-47
6.5.1-28	Reflectivities at Grazing Incidence	6.5.1-47
6.5.1-29	Neutron-Induced Swelling in Aluminum	6.5.1-50
6.5.1-30	Neutron-Induced Swelling in Magnesium	6.5.1-50
6.5.1-31	Void Swelling at High Temperature	6.5.1-51
6.5.1-32	Top View of GIMM with Scaled Measurements	6.5.1-52
6.5.1-33	Cross-Sectional View of GIMM	6.5.1-53
6.5.1-34	Detailed Cross-Section of GIMM	6.5.1-54
6.5.1-35	Section View of Mirror Structure Illustrating Expansion Capability	6.5.1-54
6.5.1-36	Thermal Design of the GIMM	6.5.1-58
6.5.1-37	Surface Deformation of Mirror	6.5.1-60
6.5.2-1	The Prometheus-H Heavy Ion Driver consists of a single beam LINAC operated in a burst mode to generate 18 beamlets, 12 storage rings, focusing magnets, and two channel transport for a 2-sided indirect drive DT target	6.5.2-2
6.5.2-2	Schematic of the Prometheus-H Quadrupole Focusing Channel	6.5.2-3
6.5.2-3	Heavy Ion Trajectories Lie Within this Elliptical Envelope in Phase Space	6.5.2-4
6.5.2-4	Relationships Between Magnetic Fields at Poletips, Walls, and Wires	6.5.2-5
6.5.2-5	Relationship Between Particle Energy, V, and Accelerator Gradient, G, in LINAC	6.5.2-6
6.5.2-6	Heavy Ion beam current as a function of time at a given location in the Prometheus Heavy Ion Driver	6.5.2-6
6.5.2-7	Dependence of accelerator gradient on the displacement along the LINAC axis, z, in the ramp-gradient section of the Prometheus-H heavy ion driver	6.5.2-12
6.5.2-8	Variation of heavy ion beam energy with distance along accelerator axis in ramp-gradient portion of accelerator	6.5.2-12
6.5.2-9	Variation of beam energy with displacement along axis for both ramped gradient and constant gradient accelerators	6.5.2-13
6.5.2-10	Depressed tune, σ , vs. displacement along the LINAC axis	6.5.2-14
6.5.2-11	G_r as a function of displacement along LINAC axis	6.5.2-14
6.5.2-12	Variations of Displacement between Quads (L), blank space between Quads (space) and Quadrupole Length (q) as functions of displacement along accelerator axis	6.5.2-15
6.5.2-13	Variation of Quad Packing Fraction (η) and Quad Aspect Ratio (a/l) as functions of displacement along LINAC axis (z)	6.5.2-15
6.5.2-14	Dependence of HI beam current (I) and pulse duration (τ) on location along LINAC axis (z)	6.5.2-16
6.5.2-15	Pulse length (τ) of HI beam as a function of displacement along LINAC axis (z)	6.5.2-16
6.5.2-16	Comparison of Multiple Beam LINAC with Single Beam LINAC	6.5.2-18
6.5.2-17	Energy Dissipation for Metglas as a Function of (Square) Pulse Duration	6.5.2-19
6.5.2-18	Metglas Heat as a Function of PRF	6.5.2-20
6.5.2-19	Damping Resistor Circuit on LINAC (Similar to LLNL ATA Design)	6.5.2-21
6.5.2-20	Evolved Pulsed Power Component Configuration to Limit Failures	6.5.2-22

McDonnell Douglas Aerospace

LIST OF FIGURES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.5.2-21	Prometheus-H Superconducting cos (20) Quadrupole Core Configuration	6.5.2-23
6.5.3-1	Conceptual Design of Neutron Pinhole to Limit Neutron Propagation into Driver Building.....	6.5.3-3
6.5.3-2	Common Enclosure of Heavy Ion Beams Provides Plenum for Attaining 10 ⁻⁵ torr Pressure Level.....	6.5.3-4
6.5.3-3	Prometheus Instrumentation and Control Methodology.....	6.5.3-7
6.5.3-4	Shielding of Final Laser Optics Contains Radiation Within the Beamline	6.5.3-9
6.5.3-5	Details of Heavy Ion Beam Final Focus Shielding	6.5.3-10
6.6-1	Hydrogen Pumping Speed Vs. Pump Diameter.....	6.6-3
6.6-2	Vacuum Ports Required.....	6.6-4
6.6-3	Total Active Cryogenic Pump Required Vs. Number of Vacuum Ports.....	6.6-5
6.6-4	Cryopump Hydrogen Capacity Vs. Pump Diameter	6.6-6
6.6-5	Laser-Driven Reactor Vacuum Manifold System Arrangement	6.6-7
6.6-6	Heavy Ion Reactor Vacuum Manifold Systems Arrangement.....	6.6-10
6.7.1-1	Fuel Processing Systems Arrangement.....	6.7-2
6.7.3-1	Thermally Coupled Pressure Swing Adsorption for Fuel Treatment.....	6.7-6
6.7.3-2	Laser-Based Isotope Separation System.....	6.7-9
6.7.4-1	Chamber Exhaust Purification and Impurity Treatment System.....	6.7-11
6.7.5-1	PSA Column Pressure Variation with Time	6.7-13
6.7.5-2	PSA HT Adsorbed as Function of Time	6.7-13
6.7.5-3	PSA for Tritium Extraction from Breeder.....	6.7-15
6.7.6-1	Functional Arrangement of ADS.....	6.7-17
6.7.6-2	Recombiner-Dryer Based Air Detritiation System	6.7-20
6.7.6-3	Membrane Based Air Detritiation System.....	6.7-21
6.7.7-1	Getter-Based Inert Gas Detritiation System.....	6.7-23
6.7.7-2	Recombiner/Dryer Based Inert Gas Detritiation System	6.7-24
6.7.8-1	Fuel Storage and Management System Diagram.....	6.7-26
6.7.9-1	ISS and Water Detritiation – Flow Diagram.....	6.7-28
6.7.10-1	Y.YH ₂ Formation vs. Equilibrium Hydrogen Pressure.....	6.7-37
6.7.10-2	Recovery of Tritium from Na by Yttrium Gettering.....	6.7-38
6.8-1	Perspective View of the Cavity with Laser Beams.....	6.8-3
6.8-2	Perspective View of the Cavity without Laser Beams.....	6.8-4
6.8-3	Radial Build of the Cavity.....	6.8-7
6.8.1-1	Material Composition in the 1-D Cavity Model.....	6.8.1-2
6.8.1-2	Nuclear Heating Rate Profile in the Baseline Design.....	6.8.1-5
6.8.1-3	Nuclear Heating Rate Profile in the First Wall Design.....	6.8.1-6
6.8.1-4	Nuclear Heating Rate Profile in the Blanket/Reflector/Plena System	6.8.1-6
6.8.1-5	Nuclear Heating Rate Profile in the Concrete Bulk Shield Case	6.8.1-7
6.8.1-6	Displacement Per Atom Per Full Power Year in Silicon	
6.8.1-7	Tritium Production Rate Profile in the Breeding Zone Per Incident Neutron.....	6.8.1-12
6.8.1-8	Neutron Flux in the First Wall of the FWS and in the First Wall of the Blanket/ Reflector/Plena System Per Incident Neutron	6.8.1-12
6.8.1-9	Neutron Flux in the FW of the FWS and the FW of the Blanket/Reflector/Plena System.....	6.8.1-13
6.8.1-10	Neutron Flux Above 0.2 MeV in the FW of the FWS and in the FW of the Blanket/ Reflector/Plena System per Incident Neutron.....	6.8.1-14
6.8.1-11	Neutron Flux in the FW of the FWS and in the FW of the Blanket/Reflector/Plena System.....	6.8.1-14
6.8.2-1	First Wall Panel; Cross Sectional View.....	6.8.2-1
6.8.2-2	Schematic View of Film Supply Systems	6.8.2-3
6.8.2-3	Target X-Ray Spectra Used for Prometheus-L and -H.....	6.8.2-7

McDonnell Douglas Aerospace

LIST OF FIGURES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.8.2-4	Cross Section in Pb as a Function of X-Ray Energy.....	6.8.2-8
6.8.2-5	Fraction of X-Ray Energy Absorbed by the Lead Vapor.....	6.8.2-9
6.8.2-6	Energy Deposition Profile in Pb Film.....	6.8.2-11
6.8.2-7	Integrated Energy Deposition Profile in Pb Film.....	6.8.2-12
6.8.2-8	Debris Ion Deposition Profiles in Cavity Vapor.....	6.8.2-13
6.8.2-9	Mathematical Model of the Vapor Flow in the Cavity.....	6.8.2-16
6.8.2-10	The Staggered Grid and Nodes.....	6.8.2-18
6.8.2-11	Filtering Process Applied to the CDS Result.....	6.8.2-21
6.8.2-12a	Instantaneous Uniform Pressure on the Wall with Lithium Vapor.....	6.8.2-23
6.8.2-12b	Instantaneous Uniform Pressure on the Wall with Lead Vapor.....	6.8.2-23
6.8.2-13	Energy Transport Pathways and Overall Geometry.....	6.8.2-25
6.8.2-14	Specific Energy of Pb Vapor vs. Temperature.....	6.8.2-28
6.8.2-15	Cavity Vapor Pressure and Mass Histories for Prometheus-L.....	6.8.2-30
6.8.2-16	Cavity Vapor Pressure and Mass Histories for Prometheus-H.....	6.8.2-31
6.8.2-17	Saturation Pressure of Pb and Saturation Pressure Corrected to 0°C.....	6.8.2-31
6.8.2-18	Base Case Cavity Vapor Temperature and Pressure Histories for Prometheus-L.....	6.8.2-32
6.8.2-19	Base Case Cavity Vapor Temperature and Pressure Histories for Prometheus-H.....	6.8.2-33
6.8.2-20	Base Case Temperatures at the Film Surface and Interface Between the Film and SiC Wall for Prometheus-L.....	6.8.2-34
6.8.2-21	Effect of Rep. Rate on the Cavity Pressure Following a Blast.....	6.8.2-35
6.8.2-22	Effect of Increasing the Cavity Size on the Cavity Pressure Following a Blast.....	6.8.2-35
6.8.2-23	Effect of Changing the Cavity Area with the Volume Fixed.....	6.8.2-37
6.8.2-24	Effect of Changing the Cavity Volume with the Area Fixed.....	6.8.2-37
6.8.2-25	Effect of Increasing the Cavity Volume on the Pressure History.....	6.8.2-38
6.8.2-26	Effect of Non-Condensable Gas Pressure on the Final Cavity Pressure.....	6.8.2-38
6.8.2-27	Identification of Wave Classes.....	6.8.2-41
6.8.2-28	Longitudinal Distribution of Maximum and Minimum Film Thickness.....	6.8.2-42
6.8.2-29	Baseline Pressure Distribution and Seepage Rate Along the First Wall.....	6.8.2-43
6.8.2-30	Illustration of Force Elements Acting on the Upper Wall Film.....	6.8.2-44
6.8.2-31	Minimum Required Film Velocity for Attachment on the Upper Hemisphere Wall.....	6.8.2-46
6.8.2-32	Turbulent Film Thickness and Minimum Volumetric Flow Rate for Attachment.....	6.8.2-46
6.8.2-33	Film Thickness as a Function of Distance Away from the Top End Cap.....	6.8.2-47
6.8.2-34	Average Film Velocity as a Function of Distance from the Top End Cap.....	6.8.2-47
6.8.2-35	Film Thickness as a Function of Distance Away from the Top End Cap.....	6.8.2-49
6.8.2-36	Film Velocities as a Function of Distance Away from the Top End Cap.....	6.8.2-49
6.8.2-37	Cavity and Differential Pressure Histories at the Uppermost Point of the Cavity.....	6.8.2-51
6.8.2-38	Ultimate Film Thickness and Film Velocity Histories Following the Cavity Pressure Build-Up.....	6.8.2-52
6.8.2-39	The History of the Pressure Loading on the First Wall Following the Microexplosion.....	6.8.2-54
6.8.2-40	Instantaneous Velocity and Radial Displacement of the Continuous First Wall.....	6.8.2-55
6.8.2-41	Hoop Stress History in the Continuous First Wall.....	6.8.2-56
6.8.2-42	Kinetic Energy of the Vibrating Continuous First Wall.....	6.8.2-56
6.8.2-43	Schematic of Mechanical Loading of the FW Panels.....	6.8.2-58
6.8.2-44	Instantaneous Velocity and Displacement at Center of First Wall Plate.....	6.8.2-59
6.8.2-45	The History of Stresses at Center of FW Plate.....	6.8.2-60
6.8.2-46	The History of Stresses at Clamped Edge of FW Plate.....	6.8.2-60
6.8.2-47	The Stress-Strain Diagram for SEP 2D SiC/SiC Composite.....	6.8.2-61
6.8.3-1	Schematic of a Blanket Module.....	6.8.3-1
6.8.3-2	Enlarged Breeder Region Cutaway.....	6.8.3-2
6.8.3-3	Blanket Module Internal Structure Showing Coolant and Purge Manifolds and Reinforcing Ribs.....	6.8.3-3
6.8.3-4	The Radial-Build of the Prometheus Cavity.....	6.8.3-6
6.8.3-5	Material Composition in the 1-D Cavity Model.....	6.8.3-7
6.8.3-6	Nuclear Power Multiplication as a Function of Lead Zone Thickness.....	6.8.3-9

McDonnell Douglas Aerospace

LIST OF FIGURES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.8.3-7	Tritium Breeding Ratio and Nuclear Power Multiplication as a Function of Lead Zone Thickness	6.8.3-9
6.8.3-8	Fraction of Nuclear Power Deposited in the First Wall and Blanket/Reflector Systems as a Function of Lead Zone Thickness	6.8.3-10
6.8.3-9	Fraction of Nuclear Power Deposited in the Vacuum Vessel and Shield Systems as a Function of Lead Zone Thickness	6.8.3-10
6.8.3-10	Nuclear Power Density as a Function of the Lead Zone Thickness	6.8.3-11
6.8.3-11	Nuclear Power Density as a Function of the Lead Zone Thickness	6.8.3-11
6.8.3-12	Tritium Production Rate from Li-6 as a Function of Lead Zone Thickness	6.8.3-12
6.8.3-13	Tritium Production Rate from Li-7 as a Function of Lead Zone Thickness	6.8.3-13
6.8.3-14	Nuclear Power Multiplication as a Function of the Breeding Zone Thickness	6.8.3-14
6.8.3-15	Tritium Breeding Ratio as a Function of the Breeding Zone Thickness	6.8.3-14
6.8.3-16	Fraction of Nuclear Power Deposited in the First Wall and Blanket/Reflector Systems	6.8.3-15
6.8.3-17	Fraction of Power Deposited in the Vacuum Vessel and Shield Systems	6.8.3-15
6.8.3-18	Nuclear Power Multiplication as a Function of the Beryllium Zone Thickness	6.8.3-17
6.8.3-19	Tritium Breeding Ratio as a Function of Beryllium Zone Thickness	6.8.3-17
6.8.3-20	Fraction of Nuclear Power Deposited in the First Wall and Blanket/Reflector Systems as a Function of Beryllium Zone Thickness	6.8.3-18
6.8.3-21	Fraction of Nuclear Power Deposited in the Vacuum Vessel and Shield Systems as a Function of Beryllium Zone Thickness	6.8.3-18
6.8.3-22	He Coolant Velocity in the Blanket as a Function of the Inlet Pressure for Different Fractional Flow Areas	6.8.3-19
6.8.3-23	He Coolant Pressure Drop in the Blanket as a Function of the Inlet Pressure for Different Fractional Flow Areas	6.8.3-21
6.8.3-24	He Purge Pressure Drop in the Blanket as a Function of the Li ₂ O Bed Packing Fraction for Different Purge Inlet Pressures	6.8.3-22
6.8.3-25	Cross-Section of the Module Front Wall Showing the He Cooling Channels	6.8.3-23
6.8.3-26	Thermal Stress in the Module Wall as a Function of the Distance Between the Coolant Channel and the Wall Edge	6.8.3-24
6.8.3-27	Maximum Bending Stress in a Plate with Built-In Edges as a Function of the Plate Width for Different Plate Thicknesses	6.8.3-26
6.8.4-1	Neutrons and Gamma Ray Fluxes in the Concrete Bulk Shield as a Function of Depth Inside the Bulk Shield	6.8.4-3
6.8.4-2	Neutron and Gamma Ray Fluxes in the Composite Bulk Shield as a Function of Depth Inside the Shield	6.8.4-3
6.8.5-1	Cavity Cross-Section and Zone Designation	6.8.5-3
6.8.5-2	Radioactivity Calculational Procedure	6.8.5-4
6.8.5-3	Specific Radioactivity in the First Wall System	6.8.5-9
6.8.5-4	Specific Radioactivity in the Blanket and Reflector	6.8.5-9
6.8.5-5	Specific Radioactivity in the Vacuum Vessel, Shield, and Surrounding Air	6.8.5-10
6.8.5-6	Integrated Radioactivity in Each Component as a Function of Time After Shutdown	6.8.5-12
6.8.5-7	Comparison of Activation Levels Between Prometheus and Conventional Concrete Shield	6.8.5-13
6.8.5-8	Neutron Flux Comparison Between Prometheus and Conventional Concrete Shield	6.8.5-14
6.8.5-9	Photon Flux Comparison Between Prometheus and Conventional Concrete Shield	6.8.5-14
6.8.5-10	Cylindrical Modeling of the Cavity	6.8.5-15
6.8.5-11	Specific BHP in the First Wall System	6.8.5-17
6.8.5-12	Specific BHP in the Blanket and Reflector	6.8.5-18
6.8.5-13	Specific BHP in the Vacuum Vessel, Shield, and Surrounding Air	6.8.5-18
6.8.5-14	Po ²¹⁰ Buildup in the Prometheus First Wall System	6.8.5-21
6.8.5-15	Specific Decay Heat Histories at Different Components	6.8.5-23
6.8.5-16	Temperature Histories at SiC FW and Blanket Components Following a Loss of Coolant Accident	6.8.5-24

McDonnell Douglas Aerospace

LIST OF FIGURES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.8.5-17	Scenarios of Dry Spot Formation Which Lead to a Reactor Shutdown	6.8.5-28
6.8.5-18	The Energy Available for Sublimation Is the Difference Between the Radiative and Conductive Heat Fluxes	6.8.5-29
6.9-1	Prometheus Baseline Power Flow	6.9-2
6.9-2	Prometheus-L Energy Conversion System	6.9-3
6.9-3	Prometheus-H Energy Conversion System	6.9-3
6.9-4	Prometheus-L Turbine Thermal Cycle	6.9-5
6.9-5	Prometheus-H Turbine Thermal Cycle	6.9-6
6.9-6	Coolant Distribution and Steam Generation	6.9-10
6.9-7	Steam Generation Flow Schematic	6.9-10
6.9-8	Helium Heat Exchanger Module	6.9-11
6.9-7	Vessel #1, Helium Steam Generator	6.9-12
6.9-10	Vessel #4, Liquid Lead Steam Generator	6.9-14
6.9-11	Liquid Lead Heat Exchanger - Cross Section	6.9-15
6.9-12	Liquid Lead Steam Generator - Top Tube Sheet Connections	6.9-15
6.9-13	Helium System Cost vs. Circulating Power	6.9-20
6.10-1	Prometheus Control Complex	6.10-9
6.11-1	In-Vessel Vehicular System Represents Current State-of-the-Art in Manipulator Technology	6.11-2
6.11-2	Remote Manipulators Performing Typical Maintenance Tasks of INTER	6.11-3
6.11-3	Maintenance Manipulators and Vehicle at the JET Facility	6.11-4
6.11-4	SPAR 2500 and Schilling Manipulator at the DOE Hanford Facility	6.11-5
6.11-5	MASCOT, a Typical Small Nuclear Manipulator at the JET Fusion Facility	6.11-6
6.11-6	Curved Deployable X-Boom Truss	6.11-8
6.11-9	STEM Mounted Camera	6.11-9
6.11-9	Mobile Folding Crane	6.11-12
6.11-10	Deployable Crane Hoist	6.11-13
6.11-11	Heavy Crane with Removable Drives	6.11-14
6.11-12	Typical Remote Handling Tool (JET Pipe Cutter)	
6.11-13	Upper Reactor Manipulator	6.11-17
6.11-14	Deployable Heavy Duty Manipulator	6.11-19
6.11-15	Mobile Heavy Duty Manipulator	6.11-20
6.11-16	Two-Arm Dexterous Manipulator	6.11-22
6.11-17	Small Power Manipulator	6.11-23
6.11-18	Steam Generator Robot	6.11-24
6.13-1	Unit Cost Reduction Factors for 70, 80, and 90% Learning	6.13-2
6.13-2	Change in Prometheus COE for Different LSA Assumptions	6.13-5
6.13-3	Change in Prometheus COE for Different Plant Electric Power Outputs	6.13-6
7-1	Evaluation Methodology Approach	7-3
7-2	Safety and Environment Evaluation Approach	7-8
C-1	Log Linear Unit Cost Curves	C-11
C-2	Radial Build of the First Wall, Blanket, and Shield Subsystems	C-22

LIST OF TABLES – VOL. III

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.5.1-1	Prometheus ELMO Specifications.....	6.5.1-7
6.5.1-2	Prometheus ELP Specifications.....	6.5.1-13
6.5.1-3	Prometheus ELD Specifications.....	6.5.1-14
6.5.1-4	Prometheus ELPA Specifications.....	6.5.1-15
6.5.1-5	Common Raman Amplifier Specifications.....	6.5.1-17
6.5.1-6	Prometheus Local Raman Oscillator Specifications.....	6.5.1-19
6.5.1-7	Prometheus Raman Preamplifier Specifications.....	6.5.1-19
6.5.1-8	Prometheus Raman Accumulator Specifications.....	6.5.1-21
6.5.1-9	Energy Distribution in Excimer Laser Pumping.....	6.5.1-33
6.5.1-10	Excimer Laser Optical Subsystems.....	6.5.1-34
6.5.1-11	Potential Damage Sources for Final Turning Optics.....	6.5.1-39
6.5.1-12	Reflectivity for Materials of Interest (Polished Surfaces).....	6.5.1-46
6.5.1-13	Thermal-Hydraulic Parameters for the GIMM.....	6.5.1-55
6.5.2-1	Summary of Heavy Ion Driver Parameters.....	6.5.2-8
6.5.2-2	Summary of Injector Parameters.....	6.5.2-9
6.5.3-1	Pulsed Power Requirements for EDEL.....	6.5.3-1
6.5.3-2	EDEL Ceramic PFL Design Parameters.....	6.5.3-2
6.5.3-3	Laser Pulsed Power System Efficiency Summary.....	6.5.3-2
6.6-1	Laser Driven Reactor Vacuum System Design Requirements.....	6.6-2
6.6-2	Heavy Ion-Driven Reactor Vacuum System Requirements.....	6.6-8
6.7.1-1	FPS Design Data-L - Laser Option – Stream Identification is Consistent with Figure 6.7.1-1.....	6.7-3
6.7.1-2	Fuel Processing Services and Proposed Technologies for Prometheus IFE.....	6.7-4
6.7.6-1	ADS Design Parameters.....	6.7-18
6.7.8-1	Tritiated Hydrogen Storage Requirements.....	6.7-25
6.7.8-2	Tritium Storage Tank Requirements.....	6.7-26
6.7.9-1	Water Distillation Column Parameters.....	6.7-31
6.7.9-2	Cryogenic Distillation Column Parameters.....	6.7-33
6.7.9-3	ISS Liquid Flows, L-Option.....	6.7-34
6.7.9-4	ISS Gas Flows, L-Option.....	6.7-34
6.7.9-5	ISS Liquid Flows, H-Option.....	6.7-34
6.7.9-6	ISS Gas Flows, H-Option.....	6.7-34
6.7.9-7	Failure Modes and Effects Analysis for the ISS.....	6.7-36
6.7.9-8	Heat Transfer Media Must Be Processed to Keep Tritium Permeation Within Acceptable Limits.....	6.7-36
6.8.1-1	Key Neutronics Parameters for Prometheus-L and Prometheus-H.....	6.8.1-5
6.8.1-2	Nuclear Heating in Prometheus First Wall/Blanket/Shield Systems.....	6.8.1-9
6.8.1-3	Cavity Energy Balance.....	6.8.1-10
6.8.2-1	First Wall System Major Parameters.....	6.8.2-4
6.8.2-2	First Wall Power Balance.....	6.8.2-4
6.8.2-3	First Wall System Thermal Hydraulic Parameters.....	6.8.2-6
6.8.2-4	Chamber Parameters (Base Cases).....	6.8.2-8
6.8.2-5	Mass and Thickness of Layer Vaporized by X-Rays.....	6.8.2-11
6.8.2-6	Target Debris Ion Spectra and Masses.....	6.8.2-13
6.8.2-7	The Function A(Pe) for Different Schemes.....	6.8.2-20
6.8.2-8	Properties of Liquids Used in Hydrodynamics Calculations.....	6.8.2-22
6.8.2-9	Base Case Parameters.....	6.8.2-32
6.8.2-10	Summary of Cases Analyzed.....	6.8.2-47
6.8.2-11	Properties of SEP-2D SiC-SiC.....	6.8.2-53
6.8.3-1	Final Blanket Performance Parameters.....	6.8.3-4
6.8.3-2	Properties of SiC Composite Used in the Stress Calculations.....	6.8.3-24

McDonnell Douglas Aerospace

LIST OF TABLES – VOL. III (CONT.)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6.8.3-3	Input Used in MISTRAL to Calculate the Blanket Tritium Inventory Results	6.8.3-27
6.8.3-28	Tritium Inventory as a Function of the Activation Energy of Solution for Constant Heat of Adsorption	6.8.3-29
6.8.3-29	Tritium Inventory as a Function of the Heat of Adsorption for Constant Activation Energy of Solution	6.8.3-29
6.8.5-1	Cavity Failure Modes and Consequences	6.8.5-2
6.8.5-2	Zonal Specific Radioactivity as a Function of Post Shutdown Times After 30 Years Full Operation	6.8.5-6
6.8.5-3	Reaction Products Resulting from the Neutron Irradiation of Reactor Materials	6.8.5-8
6.8.5-4	Zone-Averaged ¹⁴ C Radioactivity Level in Breeding Zone After 30 Years	6.8.5-11
6.8.5-5	Radioactivity of Po ²¹⁰ With Other Dominating Nuclides in the Pb Film	6.8.5-20
6.8.5-6	BHP of Po ²¹⁰ With Other Dominating Nuclides in the Pb Film	6.8.5-20
6.8.5-7	Summary of Passive Lead Decay Heat Removal Systems	6.8.5-25
6.9-1	Turbine Input Conditions	6.9-4
6.9-2	Auxiliary Power Requirements	6.9-8
6.9-3	Performance	6.9-8
6.9-3	Helium Pipe Costs	6.9-19
6.9-4	Key Helium System Valves	6.9-20
6.10-1	Cooling Tower System Design Parameters	6.10-4
6.12-1	ESECOM Threshold Dose Release	6.12-13
6.12-2	NRC Compliance Parameters	6.12-15
6.13-1	Cost Summaries for Prometheus-L and -H Power Plants	6.13-3
6.13-2	Indirect Cost Factors for Different LSA Values	6.13-5
7-1	Engineering Feasibility Evaluation	7-5
7-2	Scoring System for Engineering Feasibility	7-6
7-3	Safety and Environmental Evaluation Indices and Weights	7-9
7.3.2-1	Physics Feasibilities of Laser and Heavy Ion Drivers	7-15
7.3.3-1	Engineering Feasibility Evaluation	7-17
7.3.5-1	Safety and Environment Comparison	7-22
7.3.6-1	Summary of Key Items of Costs of R&D for Laser and Heavy Ion Reactors	7-24
7.3.7-1	Summary of Scores for the Five Evaluation Areas	
C-1	Economic Requirements and Criteria	C-2
C-2	Commerce Department Gross National Product Implicit Price Level Deflators	C-2
C-3	Prometheus Plant Cost Accounts	C-3
C-4	Application of Learning Curve by Cost Account	C-12
C-5	Site Improvements and Facilities Costs	C-18
C-6	Cost of Materials Used in the FW/B/S Systems	C-23
C-7	First Wall and Blanket Material Costs	C-23
C-8	Cost of Shield Materials Comparison	C-24
C-9	Total Shielding and Vacuum Vessel Costs	C-25
C-10	Primary Structure Weights and Costs	C-26
C-11	Main Heat Transfer and Transport System Costs	C-28
C-12	Reactor Plant Maintenance	C-31
C-13	Turbine Plant Cost Estimating Relationships	C-33
C-14	Target and Target Plant Cost Factors	C-34
C-15	Driver Plant Equipment Costs	C-35
C-16	Prometheus Reactor Plant Cost Factors in Constant 1991 Dollars	C-36
C-17	Cost of Electricity Accounts for the Prometheus Reactor Plants	C-37

McDonnell Douglas Aerospace